



**VOSS**



**VOSS Insights  
DS9 for NetFlow Install Guide**

**Release 24.1**

May 29, 2024

## Legal Information

- Copyright © 2024 VisionOSS Limited. All rights reserved.
- This information is confidential. If received in error, it must be returned to VisionOSS ("VOSS"). Copyright in all documents originated by VOSS rests in VOSS. No portion may be reproduced by any process without prior written permission. VOSS does not guarantee that this document is technically correct or complete. VOSS accepts no liability for any loss (however caused) sustained as a result of any error or omission in the document.


DOCUMENT ID: 20240529153354

# Contents


- 1 NetFlow Quickstart** **1**
  - 1.1 NetFlow Setup Overview . . . . . 1
  - 1.2 NetFlow Solution Documentation . . . . . 3
  
- 2 DS9 Download** **4**
  
- 3 VOSS Insights DS9 for NetFlow Product Registration** **5**
  
- 4 VOSS Insights DS9 for NetFlow Base Environment Installation** **8**
  - 4.1 VOSS Insights DS9 Standalone Installation . . . . . 8
  
- 5 Prepare a Production Environment for NetFlow** **10**
  - 5.1 Abstract . . . . . 10
  - 5.2 Checklist . . . . . 10
  - 5.3 Requirements . . . . . 12
  
- 6 DS-9 NetFlow VM Sizing Specifications** **13**
  - 6.1 Small NetFlow Solution . . . . . 13
  - 6.2 Medium NetFlow Solution . . . . . 13
  - 6.3 Large NetFlow Solution . . . . . 14
  
- 7 NetFlow and DS9 Monitoring System Connectivity** **16**
  - 7.1 Communication ports between NetFlow Source and DS9 . . . . . 16
  - 7.2 Communication ports between Dashboard Server Users and Dashboard Server . . . . . 16
  - 7.3 Communication ports between the DS9 Server and Dashboard Server . . . . . 17
  - 7.4 Communication ports that are required for remote management purposes . . . . . 17
  
- 8 Deploy and VM Installation** **18**
  - 8.1 Base Install and Configuration . . . . . 18
  - 8.2 Multi-line CUCM Cipher Support . . . . . 27
  
- 9 DS9 Configuration on the Dashboard** **29**
  
- Index** **36**

# 1. NetFlow Quickstart


## 1.1. NetFlow Setup Overview



### 1.1.1. DS9 for NetFlow Setup



### 1.1.2. Dashboard for NetFlow Setup



## 1.2. NetFlow Solution Documentation

### 1.2.1. Additional Reference Documentation

- Dashboard Release Notes
- Compatibility Matrix
- Dashboard Install Guide
- Dashboard and Arbitrator Maintenance and Upgrade Guide
- Dashboard Administration Guide
- Dashboard API Guide
- Platform Guide

## 2. DS9 Download

- DS9 OVA file:
  1. Log in on the [VOSS Customer Portal](#)
  2. Go to **Downloads > VOSS Insights > Insights DS9 Hawaii > <release number> > New Installation.**
  3. Download the .ova file
- DS9 upgrade file:
  - a. Log in on the [VOSS Customer Portal](#)
    - i. Go to **Downloads > VOSS Insights > Insights DS9 Hawaii > <release number> > Upgrade.**
    - ii. Download the .lxsp upgrade file


or

- b. Use the direct link - for automated download mechanisms:
  - i. <http://www.layerxtech.com/downloads/ds9/updates/layerX-lxts9-hawaii-sp1-sp22.1.lxsp>


To ensure continuity, the release updates will still be available from the LayerX download site, allowing customers to either download files manually, or via the automated download mechanisms from that location.

### 3. VOSS Insights DS9 for NetFlow Product Registration


1. Connect to the DS9 server using an SSH client on port 22 and login using the admin credentials to access the **Administration** menu.
2. Select the **System > Product Registration** menu.








3. Select the **Set Product Key** option to input the Product Key.



---

A terminal window with a blue header bar. The text displayed is: "The product id is: 9XYJC-RAHRD-3FC7C-TJX4D-E7EH9" followed by "Please insert the product key." on the next line. A green cursor is visible at the start of the second line.

```
The product id is: 9XYJC-RAHRD-3FC7C-TJX4D-E7EH9
Please insert the product key.
```

4. Paste the Product Key into the interface and hit <Enter> to update the licensing expiration on the DS9 Netflow server.
5. Once returned back to the **Product Registration** menu, select **Back** to navigate back to the **Administration** menu then select **Quit** to exit the interface and close the SSH session.

## 4. VOSS Insights DS9 for NetFlow Base Environment Installation

### 4.1. VOSS Insights DS9 Standalone Installation

VOSS Insights DS9 is a standalone single server to collect, process and store NetFlow-v5/v9/v10 and SNMP data. Visualization of the data will be handled via the VOSS Insights Dashboard reporting.

#### 4.1.1. Assumptions

- Host machines will be located within the same sub-network
- All the required TCP/UDP ports are open between DS9, Dashboard and NetFlow sources.
  - TCP: 5432 - 8082
  - UDP Depending on desired vflow: 2055 - 9996 - 4739 There is no redundancy requirement for any of the components
- Internet access is available to the DS9 system during installation.  
After the installation, no internet access is necessary.
- Customer premises equipment is sending NetFlow data to Collector successfully Collector can access customer premises equipment via SNMP v1/2/3 successfully

#### 4.1.2. Installation

**Items that will be needed during configuration:**

1. Hostname
2. Dashboard Reporter IP
3. For each NetFlow device added:
  - IP of device interface sending NetFlow to the DS9
  - NetFlow version
  - SNMP version
    - v1 or v2c - community string

- v3 - user name, user password, and encryption key
- NAT IP address (often same as IP )

## 5. Prepare a Production Environment for NetFlow

### 5.1. Abstract

This guide is an overview of all the action items that need to be completed by system administrators before implementation of a successful deployment.

### 5.2. Checklist

The following action items need to be completed by system administrators before the implementation starts:

ID	Action	Description	Criticality
1	Hardware specifications	The hardware/VM specifications have to meet the requirements defined by VOSS	Critical
2	Software specifications	VOSS Dashboard server is delivered as an OVA which includes an operating system. If this is a VM deployment, the following should be available in customer's VM datastore: <ul style="list-style-type: none"> <li>• Latest OVAs. (Available at <a href="#">VOSS Customer Portal</a>. Log in and select DOWNLOADS.)</li> </ul>	Critical
3	Firewall rules	All the required traffic rules are applied to customer environment based on the firewall matrix provided by VOSS deployment Team.	Critical
4	Internet access	Internet access is enabled for the DS9 during implementation. Once the implementation is over, internet access is no longer required.	Critical
5	Round trip times (RTT)	RTT time between the DS9 and Dashboard Server is not more than 100msec.	Critical
6	NetFlow configuration	NetFlow sources are configured to send their NetFlow data to VOSS DS9 Servers based on the suggested settings by VOSS	Critical
7	SNMP configuration	NetFlow sources are configured with SNMP v1 or 2c or v3.	Critical
8	NetFlow and SNMP details	Following information is provided to VOSS deployment team: <ul style="list-style-type: none"> <li>• Device IP &amp; Hostname and NetFlow version for the NetFlow source(s)</li> <li>• SNMP details for NetFlow source(s)</li> </ul>	Critical
9	Remote access	Some method of remote access is enabled for VOSS deployment team.	Critical
10	Integration to customer environment	Both DS9 and Dashboard Servers have access to customers data infrastructure for the following services: NTP, SMTP, DNS.	Critical
11	Authentication via existing customer resources	Dashboard Servers have access to customers' existing Active Directory/Identity servers to authenticate users via LDAP or SAMLv2.	Optional

## 5.3. Requirements

The following list of items needs to be provided to VOSS before the deployment:

ID	Action	Description	Criticality
1	IP Addresses for VOSS components	IP addresses & Subnetmasks & Default IP Gateway settings for all the VOSS Host Machines (DS9, Dashboard Servers).	Critical
2	IP Addresses for Data services	IP addresses for the following services: DNS, NTP, SMTP, LDAP/SAMLv2.	Critical
3	Remote access details	VPN access details for VOSS Team to access the DS9 and Dashboard remotely.	Critical
4	Primary and Secondary contact details	Primary and secondary contact details for technical and project management related items.	Critical
5	Email authentication for scheduled reports	SMTP authentication details for smart host servers.	Optional
6	SNMP community strings, versions and other details	SNMP community strings and protocol versions need to be provided to VOSS for successful SNMP queries.	Critical
7	List of NetFlow Sources	Provide VOSS a list of NetFlow sources (routers, switches) with the following details: IP addresses, Make/Model, Software Version, NetFlow version.	Critical
8	List of IP addresses and Hostnames	A CSV or Excel file that maps certain IP addresses to internal hostnames can help VOSS Team to improve the data visualization experience by mapping IP address fields to hostnames.	Optional

## 6. DS-9 NetFlow VM Sizing Specifications

VOSS Insights DS9 for NetFlow sizing specifications are divided into small, medium and large solutions based on tiers related to the number of flows that need to be supported.

Each solution below includes the VM specifications for both the VOSS Insights DS9 server and the VOSS Insights Dashboard server.

### 6.1. Small NetFlow Solution

The three small tiers in Flows per Second:

- 1,000
- 5,000
- 10,000

Dashboard Server VM		DS9 NetFlow Collector VM	
Cores	12	Cores	16
Memory GB	32	Memory	64
Disc Storage GB	500	Disc 1 OS in GB	250
SSD provisioned as Thick Eager Zero		Disc 2 Storage in GB	500
		All Discs must be SSDs and Provisioned as Thick Eager Zero	

### 6.2. Medium NetFlow Solution

Two medium tiers in Flows per Second:

- > 10,000 but <= 25,000
- > 25,000 but <= 50,000



Dashboard Server VM		DS9 NetFlow Collector Bare Metal Server (Dell R740 or Equivalent)	
Cores	16	Cores	16
		CPU Needs to be Intel Gold or better.	
Memory GB	64	Memory	196
Disc Storage GB	500	Disc 1 OS in GB	250
SSD provisioned as Thick Eager Zero		Disc 2 Storage in TB	1,5
		Read Intensive SSDs required	
		Dual Intel 10GB NIC	1
		Intel Quad 1GB NIC	1
		iDRAC Enterprise or Equivalent	
		Dual Power Supplies	

## 6.3. Large NetFlow Solution

Two large tiers in Flows per Second:

- > 50,000 but <= 100,000
- > 100,000 but <= 200,000

**Note:** The DS9 Collector requires a minimum of 2 Bare Metal Servers to collect this volume in one location.

Dashboard Server VM		DS9 NetFlow Collector Bare Metal Server 1 (Dell R740 or Equivalent)	
Cores	16	Cores	16
		CPU Needs to be Intel Gold or better.	
Memory GB	64	Memory	196
Disc Storage GB	500	Disc 1 OS in GB	250
SSD provisioned as Thick Eager Zero		Disc 2 Storage in TB	3
		Read Intensive SSDs required	
		Dual Intel 10GB NIC	1
		Intel Quad 1GB NIC	1
		iDRAC Enterprise or Equivalent Dual Power Supplies	
		Dual Power Supplies	

Bare Metal Server 2 (Dell R740 or Equivalent)	
Cores CPU Needs to be Intel Gold or better.	16
Memory	196
Disc 1 Storage in TB	3
Disc 2 Storage in TB	3
Disc 3 Storage in TB	3
Read Intensive SSDs required	
Dual Intel 10GB NIC	1
Intel Quad 1GB NIC	1
iDRAC Enterprise or Equivalent Dual Power Supplies	
Dual Power Supplies	

**Note:**

- Larger than 200K flows per second requires special pricing and configuration.
- Distributed DS9 collection is available. This may reduce the compute required at each collection location.

## 7. NetFlow and DS9 Monitoring System Connectivity

### 7.1. Communication ports between NetFlow Source and DS9

Source	Destination	Protocol	Port	Direction	Description
NetFlow Source	DS9	UDP	4739	Unidirectional	IPFIX (Optional)
NetFlow Source	DS9	UDP	2055	Unidirectional	NetFlow v9 (Optional)
NetFlow Source	DS9	UDP	9996	Unidirectional	NetFlow v5 (Optional)
NetFlow Source	DS9	UDP	6343	Unidirectional	Sflow v5 (Optional)
DS9	NetFlow Source	UDP	161	Unidirectional	SNMP queries

### 7.2. Communication ports between Dashboard Server Users and Dashboard Server

Source	Destination	Protocol	Port	Direction	Description
Dashboard users	<b>Dashboard Server</b>	TCP	443	Unidirectional	HTTPS (GUI access)

## 7.3. Communication ports between the DS9 Server and Dashboard Server

Unless the DS9 and Dashboard Servers are located in the same subnet, system administrators need to ensure the following network ports are open between these two components.

Source	Destination	Protocol	Port	Direction	Description
Dashboard Server	DS9	TCP	5432	Unidirectional	Data respository access
Dashboard Server	DS9	TCP	8082	Unidirectional	Data respository access
Dashboard Server	DS9	TCP	443	Unidirectional	DS9 System Stats and management
DS9	Dashboard Server	UDP	514	Unidirectional	DS9 System Logs

## 7.4. Communication ports that are required for remote management purposes

Source	Destination	Protocol	Port	Direction	Description
Admin users	DS9	TCP	22	Unidirectional	SSH (remote CLI access) and file transfer
Admin users	<b>Dashboard Server</b>	TCP	22	Unidirectional	SSH (remote CLI access) and file transfer
Admin users	<b>Dashboard Server</b>	TCP	443	Unidirectional	WEB access

## 8. Deploy and VM Installation

### 8.1. Base Install and Configuration


This procedure installs the base system, and involves the following tasks:

- Download the OVA.
- Deploy the OVA.
- Run the VM.
- Log in as admin.
- Change your password.
- Configure network settings.

1. Download the OVA for your system to a directory accessible by the VM client.

2. Deploy the OVA:

1. Select the downloaded OVA file, and choose a VM name.



2. Configure storage settings via the **Select storage** menu, based on the recommended hardware specifications for the required configuration.

See the *VMWare Specification and Requirements* for your system.

3. Configure the network mappings based on the recommended hardware specifications for the required configuration.

See the *VMWare Specification and Requirements* for your system.

3. Run the VM, and monitor installation of the packages (this may take some time).

```

Info: install_package : Unpacking /mnt/cd/pkg/iana-etc.lxp
Info: install_package : Unpacking /mnt/cd/pkg/nan-pages.lxp
Info: install_package : Unpacking /mnt/cd/pkg/attr.lxp
Info: install_package : Unpacking /mnt/cd/pkg/bc.lxp
Info: install_package : Unpacking /mnt/cd/pkg/berkeley-db.lxp
Info: install_package : Unpacking /mnt/cd/pkg/bglibs.lxp
Info: install_package : Unpacking /mnt/cd/pkg/bridge-utils.lxp
Info: install_package : Unpacking /mnt/cd/pkg/dhcpd.lxp
Info: install_package : Unpacking /mnt/cd/pkg/diffutils.lxp
Info: install_package : Unpacking /mnt/cd/pkg/dnapi.lxp
Info: install_package : Unpacking /mnt/cd/pkg/ethtool.lxp
Info: install_package : Unpacking /mnt/cd/pkg/expat.lxp
Info: install_package : Unpacking /mnt/cd/pkg/gmp.lxp
Info: install_package : Unpacking /mnt/cd/pkg/lsf.lxp
Info: install_package : Unpacking /mnt/cd/pkg/ndadm.lxp
Info: install_package : Unpacking /mnt/cd/pkg/ncurses.lxp
Info: install_package : Unpacking /mnt/cd/pkg/net-tools.lxp
Info: install_package : Unpacking /mnt/cd/pkg/patch.lxp
Info: install_package : Unpacking /mnt/cd/pkg/paxctl.lxp
Info: install_package : Unpacking /mnt/cd/pkg/perl-SSLeay.lxp
Info: install_package : Unpacking /mnt/cd/pkg/popt.lxp
Info: install_package : Unpacking /mnt/cd/pkg/speex.lxp
Info: install_package : Unpacking /mnt/cd/pkg/strace.lxp
Info: install_package : Unpacking /mnt/cd/pkg/tar.lxp

```

Once all packages are installed, the VM is automatically powered off, confirmed via the `auto-poweroff` message on the console.

```

DHCPDISCOVER on eth0 to 255.255.255.255 port 67
DHCPDISCOVER on eth0 to 255.255.255.255 port 67
DHCPDISCOVER on eth0 to 255.255.255.255 port 67
DHCPDISCOVER on eth0 to 255.255.255.255 port 67
DHCPDISCOVER on eth0 to 255.255.255.255 port 67
DHCPDISCOVER on eth0 to 255.255.255.255 port 67
DHCPDISCOVER on eth0 to 255.255.255.255 port 67
DHCPDISCOVER on eth0 to 255.255.255.255 port 67
No DHCPOFFERS received.
Unable to obtain a lease on first try. Exiting.
useradd: user 'admin' already exists
mount: /mnt/target/dev: device is busy

```

The system reboots. Wait until you see the **About** console, which displays placeholder values for hostname, version, license, days licensed and remaining, and so on.

```

About
-----
Hostname: <hostname>
Version: <version>
Theme: <theme>
Flavor:
License: NNNNN-NNNNN-NNNNN-NNNNN-NNNNN

```

(continues on next page)

(continued from previous page)

```

Days Licensed: nnnnn
Days Remaining: nnnnn
Product Key:
  Website: <website>
  Kernel: Linux n.nn.nn-lxt-3 x86_64 GNU/Linux

<hostname> login:

```

#### 4. Log in:


- On the **About** console, at **<hostname> login:**, log in as admin. For the password, use the last 10 characters of the value at **License**, *excluding the dash*.

---

**Important:** The **License** key value is *only* displayed on the **About** console. When you *ssh* in, it is not visible, thus, you must copy the admin password from the **About** console.

---

- Once logged in, the **Administration** menu displays (the image displays an example for DS9):




#### 5. Change your password:

On the **Administration** menu, select **Change Passwords**, then change your password.

---


#### Note:

- It is strongly recommended that you change your password immediately.
- The **Reset GUI admin user** option on the allows for this admin user's password reset.




6. Configure network settings:

1. On the **Administration** menu, select **Network Configuration**.
2. Configure interface settings via the **Interface Settings** menu:
  1. Select the relevant interface.




2. Select **IPs**, then set the IP address and netmask in the format `nn.nn.nn.nn/24`, and save your changes.







3. Configure the default gateway via the **Extra Routes** menu.




- Use the following format for the entry: *default <gateway IP address>*
- The word *default* is required. For additional route entries use the *<subnet> <gateway>* format. Similar to what would be done on a Linux system at the CLI.




4. Configure DNS settings via the **DNS Settings** menu:



1. Select **DNS Servers**.




2. Add the IP address for each DNS server, one per line, then click **OK**.



3. Click **Save**.



5. Configure the hostname via the **Hostname** menu, then save to trigger the update.  
The console displays a message, *Updating hosts*. This setup may take a few minutes.




6. Update SSL ciphers via the **Apache Config** menu.

```
SSLCipherSuite HIGH: !MEDIUM: !ADH: !LOW
```

**Note:**

- SSLCipherSuite defaults to HIGH encryption.
- For SSLProtocol, only TLSv1.2 is supported.
- OpenLDAP defaults to HIGH encryption.
- OpenSSH does not support weak ciphers.



7. Configure SSH settings via the **SSH Config**.

Custom entries can be added, if required. The following entries have been added:

```
kexalgorithms
diffie-hellman-group14-sha1
diffie-hellman-group-exchange-sha1
hostkeyalgorithms
ssh-rsa
```

8. Configure SSHD via the **SSHD Config** menu.

**Note:**

- Multi-line entries can be added, if required. For example, for CUCM v11.5 support, see: [Multi-line CUCM Cipher Support](#).
- This step is relevant *only* to an Insights Assurance solution and its integration with Cisco UC systems. This step is *not* relevant to the DS9 and Insights NetFlow solution.

9. Enable/disable FTPD or restart the FTPD daemon:

1. On the **Administration** menu, select **Network Configuration**.
2. Select **FTPD Config**.

**Important:** On new installs, the FTPD daemon is disabled by default.

It is strongly recommended that the FTPD daemon remains disabled, unless there is a good reason you need to use it. It has been seen that enabling the FTPD daemon may introduce a system vulnerability.

FTPD is typically *only* required in rare situations, where FTP is the only way to transfer files to the server. Instead of using FTPD, it is recommended that you use the drop account with SCP or SFTP.

The drop account username is “drop”. You can set the password via the **Administration** menu.



7. Base system installation is now complete. Select **Quit** to exit the **Administration** menu on the console.

Continue with product registration, and with the configuration of your system through the GUI:

- Insights Dashboard  
See the VOSS Automate Database Setup section in the VOSS Insights Install Guide.
- Insights Arbitrator (relevant only to an Insights Assurance solution and its integration with Cisco UC systems)  
See the Install Arbitrator System section in the VOSS Insights Install Guide.
- Insights DS9

---

**Note:** Prior to opening the DS9 GUI, reboot the system.

---

See the DS9 Product Registration and Configuration on the Dashboard section in the VOSS Insights DS9 for NetFlow Install Guide.

## 8.2. Multi-line CUCM Cipher Support

This section provides details for the use of the **SSHD Config** menu option.

---

**Note:** This section is not relevant to the DS9 and Insights NetFlow solution. This solution is relevant only to an Insights Assurance solution and its integration with Cisco UC systems.

---

You can copy the keys into the screen in a comma separated list (without spaces).

For CUCM v11.5 support:

```
kexalgorithms diffie-hellman-group1-sha1,diffie-hellman-group14-sha1,diffie-hellman-  
↪group-exchange-sha1  
ciphers aes128-cbc,3des-cbc,aes128-ctr,aes192-ctr,aes256-ctr,aes128-gcm@openssh.com,  
↪aes256-gcm@openssh.com  
macs hmac-md5,hmac-sha1,hmac-sha2-256,hmac-sha1-96,hmac-md5-96  
hostkeyalgorithms ssh-rsa,ssh-dss
```

## 9. DS9 Configuration on the Dashboard

To complete the configuration between the Insights Dashboard Reporter and DS9, flow devices and SNMP configuration can be carried out:

1. Log in on the Dashboard GUI as admin, then go to **admin > Configuration**. On the **Configuration Settings** page, select the **DS9** tab.

The screenshot shows the configuration interface for DS9. At the top, there is a navigation bar with buttons for Archive, DS9 (selected), DS9 Flow Summary, Import, LDAP, Sendmail, SNMP, Syslog, VOSS, and Widget Resources. Below this, there are Save and Delete buttons. On the left, a sidebar menu lists various configuration options: About info (selected), Automatic mapping updates, Display configuration, Flow device intake, Set monitor device, Remote database access, Remote database location, Remove DS9 from reporter, Service restart, Setup new DS9, and Snmp data collection for flow device. The main content area has a yellow notification bar stating 'Changes have been made to this configuration item'. Below this, the 'About info' section is visible, with the instruction 'Obtain information from the specified DS9.' and a form field for 'ds9IpAddress'. A 'Show' button is located below the form field.

2. Choose **Setup new DS9**, add the **ds9IpAddress**, then click **Add**. Repeat this step according to the number of DS9 systems to be utilized in the environment.



- About info
- Automatic mapping updates
- Display configuration
- Flow device intake
- Set monitor device
- Remote database access
- Remote database location
- Remove DS9 from reporter
- Service restart
- Setup new DS9**
- Snmp data collection for flow device

Changes have been made to this configuration item

### Setup new DS9

Base DS9 setup, configuration done on DS9 and dashboards and data sources created on reporter.

**ds9IpAddress**

*Required - Ip address of DS9.*


**ldapPassword**

*Required - Ldap password.*

**Add**

*To let the box know about the new datasources please refresh the browser. Use Display configuration option to confirm Remote database access to this reporter.*

3. Refresh the Dashboard browser page and from the menu, select **Data Sources**.  
The new entries for the IP address are listed as DS9 SNMP . . . , DS9 SUMMARY . . . DS9 TOPN . . . entries.
4. Under the **DASHBOARDS** menu, the new **DS9 - <IP>** dashboard menu shows, for example:



Note at this stage the sub-menus are still empty.

5. Set up the DS9 to receive netflow from the source devices sending to the DS9. Go to **admin > Configuration** and on the **Configuration Settings** page, select the **DS9** tab.
6. Choose **Flow device intake** and for each remote netflow device that the DS9 server will receive flow data, set up **ds9IpAddress**, **remotelportaddress** and **port** and click **Add**.

Save Delete

- About info
- Automatic mapping updates
- Display configuration
- Flow device intake**
- Set monitor device
- Remote database access
- Remote database location
- Remove DS9 from reporter
- Service restart
- Setup new DS9
- Snm data collection for flow device

Changes have been made to this configuration item

**Flow device intake**

To configure flow injection.

**ds9IpAddress**

*Required - Ip address of DS9.*

**IdapPassword**

*Required - Ldap password.*

**Show**

Show

*Shows list of ip addresses configured to recieve flow.*

**remotelpAddress**

*Ip address to allow access. Supports comma seperated list. This is required for Add or Delete below.*

**port**

*Required for Add. Netflow 5 = 9996; Netflow 9 = 2055; Netflow 10 = 4739; Sflow = 6343.*

**Add**

Add

*Sends request to DS9, use Show for confirmation.*

**Delete**

Delete

*Sends request to DS9, use Show for confirmation.*

7. NetFlow source device interface utilization statistics that are gathered using SNMP data collection is also required. Choose the **Snm data collection for flow device** menu, enter data into the fields

---

according to your SNMP version configuration preferences, then click **Add**.

Repeat this step for each of the flow sources set up to send flow to the DS9.

Specify the same IP address of the NetFlow source to be queried in the **deviceIpAddress** field and the **snmplpAddr** field if NAT is not being used to connect to the NetFlow source device from the DS9 system.

If NAT is used to connect to the NetFlow source device, specify the NAT IP address of the NetFlow source device in the **snmplpAddr** field to use as the Ip address to connect to the system for the SNMP query.

Input the real IP address of the system into the **deviceIpAddress** field and then input the SNMP authentication parameters.

Click the **Add** button when complete.

Repeat for each NetFlow source device to be queried. The authentication parameters will cache in the browser so only changing the **deviceIpAddress** and **snmplpAddr** fields is usually required for a new entry.

Changes have been made to this configuration item

### Snmp data collection for flow device

Optional but allows for interface details to be displayed.

**ds9IpAddress**

*Required - Ip address of DS9.*

**Show**

Show

*Show status of snmp collection.*

**Enable**

Enable

*Sends request to DS9, use Show for confirmation.*

**Disable**

Disable

*Sends request to DS9, use Show for confirmation.*

**Show configured**

Show configured

*Show ip addresses of devices configured for snmp collection.*

**deviceIpAddress**

*Ip address of device to allow snmp collection. This is required for Add or*



**Delete**

Delete

Sends request to DS9, use Show configured for confirmation.

**Select an option**

- SNMPv1
- SNMPv2c
- SNMPv3

Select the SNMP version. Access from the specified DS9 to this device m

**snmpIpAddr**

Same as snmpIpAddress above but can be different. Ex. For NAT.

**userName**

**authProtocol**

Select authentication protocol.

**authPassPhrase**

# Index

## F

### Flowchart

Dashboard for NetFlow Setup, 3

DS9 for NetFlow Setup, 2

NetFlow Setup Quickstart, 1