



VOSS

VOSS Migrate

VOSS Migrate VMWare Requirements

Jan 19, 2026

Copyright © 2026 VisionOSS Limited. All rights reserved.

Contents

Introduction	2
Outbound communications	2
Inbound communications	2

Introduction

The VMWare requirements for VOSS Migrate are as follows:

- 16GB RAM
- 100GB HDD space (Thick provisioned, eager zeroed)
- 4vCPU
- Fixed IP address

Important: The specification detailed in this document is based on multiple potential projects but may require adjustment if several projects are excessively large or many projects are being used concurrently.

Outbound communications

The table describes outbound communications to external systems from VOSS Migrate:

Communication	Protocol	Network protocol and Port(s)
VOSS Automate	HTTPS	TCP 443
Cisco Unified Communications Manager (UCM)	HTTPS	TCP 443, TCP 8443
PBX Manager (if required)	Database	TCP 1433 (default)
SFTP as required for backup destinations	SFTP	TCP 22
SNMP	SNMP	UDP 162 (User definable via CLI)
NTP	NTP	UDP 123
ICMP for selected connectivity checks	ICMP	N/A

Inbound communications

The table describes inbound communications from external systems to VOSS Migrate:

Communication	Protocol	Network protocol and Port(s)
Web Access	HTTP, HTTPS	TCP 80, TCP 443
SSH/SFTP	SSH/SFTP	TCP 22
SNMP	SNMP	UDP 161