



# VOSS-4-UC 20.1.1 Release

## Changes and Impact

26 August 2020

Version 1.0

## Legal Information

Please take careful note of the following legal notices:

- Copyright © 2020. VisionOSS Limited. All rights reserved.
- VOSS, VisionOSS and VOSS-4-UC are trademarks of VisionOSS Limited.
- No part of this document may be reproduced or transmitted in any form without the prior written permission of VOSS.
- VOSS does not guarantee that this document is technically correct, complete, or that the product is free from minor flaws. VOSS endeavors to ensure that the information contained in this document is correct, whilst every effort is made to ensure the accuracy of such information, VOSS accepts no liability for any loss (however caused) sustained as a result of any error or omission in the same.
- This document is used entirely at the user's own risk. VOSS cannot be held responsible or liable for any damage to property, loss of income, and or business disruption arising from the use of this document.
- The product capabilities described in this document and the actual capabilities of the product provided by VOSS are subject to change without notice.
- VOSS reserves the right to publish corrections to this document whenever VOSS deems it necessary.
- The terms *Cisco* and all other vendors/product names mentioned in this document are registered trademarks and belong to their respective owners. VOSS does not own, nor is related to, these products and vendors. These terms have been included to showcase the potential of the VOSS solution and to simplify the deployment of these products with VOSS should you choose to utilize them.

## Security Information

This product may contain cryptographic features that may be subject to state and local country laws that govern the import, export, transfer, and use of such features. The provision of this software does not imply that third-party authorization to import, export, distribute or use encryption in your particular region has been obtained. By using this product, you agree to comply with all applicable laws and regulations within your region of operation. If you require further assistance, please contact your dedicated VOSS support person.

## Contents

[Overview](#)

[Preparing for the upgrade](#)

[API integration](#)

[Bulk load worksheets](#)

[Configuration Templates](#)

[Field Display Policies](#)

[Access Profiles](#)

[Menu Layouts](#)

[Landing Pages](#)

[User Management](#)

[Model Changes](#)

[RBAC and Configuration Changes](#)

[Data Syncs](#)

[Menu Layouts](#)

[Landing Pages](#)

[Access Profiles](#)

[Configuration Templates](#)

[Field Display Policies](#)

[Number Inventory](#)

[Schema changes](#)

[Status](#)

[Usage](#)

[Release Date](#)

[Vendor](#)

[Model Changes](#)

[Adaptations](#)

[Appendix A - data/User Schema](#)

[Appendix B - data/InternalNumberInventory Schema](#)

## Overview

The VOSS-4-UC 20.1.1 release introduces some breaking changes to various interfaces for some of its core features. This document outlines these changes in detail in order for system administrators to make necessary preparations for an upgrade to this version.

The following features have been reworked/updated

- User Management
- Number Inventory

and this impacts the following

- API integration
- Bulk load worksheets
- Configuration Templates
- Field Display Policies
- Access Profiles
- Menu Layouts
- Landing Pages

## Preparing for the upgrade

In order to sufficiently prepare for the upgrade, it is recommended to review this document in detail and take note of any changes that could impact any integrations or customizations made to the existing platform.

We recommend that a staging or lab environment is created to match the production system as close as possible and this be upgraded first. This can be done through a backup and restore onto a standalone system.

### API integration

The schema changes described below will result in a change in API behaviour. Depending on the specific usage of the endpoints and fields, will determine whether code changes will be required to any API client.

## Bulk load worksheets

Any bulk load worksheet referencing an affected model as described below, will need to be updated. New bulk load templates can be exported from an upgraded system in order to determine the new columns to be used.

## Configuration Templates

Any configuration template with an affected target model will need to be reviewed and potentially updated. It is recommended to export all customized configuration templates before performing the upgrade.

In particular, Configuration Templates for `relation/HcsUserRel` are migrated to `relation/User` and legacy fields are mapped to new fields, but the Configuration Template need to be updated manually with special attention paid to the macros used.

Configuration Templates for `data/InternalNumberInventory` specifying 'used' and 'available' fields are not migrated, but logged in the `upgrade_db.log` file.

## Field Display Policies

Any field display policy with an affected target model will need to be reviewed and potentially updated. It is recommended to export all customized configuration templates before performing the upgrade.

## Access Profiles

All access profiles will be automatically updated. It is recommended however to export all customized access profiles before the upgrade.

## Menu Layouts

All menu layouts will be automatically updated. It is recommended however to export all customized access profiles before the upgrade.

## Landing Pages

All landing pages will be automatically updated. It is recommended however to export all customized access profiles before the upgrade.

## User Management

User management in 20.1.1 has been reworked to simplify interfaces and backend workflows in order to improve overall usability. To this end, various underlying data models, capturing different aspects of a user's information, are consolidated into a single data model.

Any API integration or bulk load sheets making use of the models below will stop working when upgrading to version 20.1.1.

### Model Changes

The following models are being deprecated and consolidated into the data/User data model

- data/NormalizedUser
- data/HcsUserProvisioningStatusDAT
- data/LdapUser
- data/SsoUser
- data/UserAuthMethod
- data/HcsAdminUserDAT
- relation/HcsUserREL
- relation/HcsAdminUserREL

The following model has been deprecated

- view/HcsAuditUserSyncToVIEW

The following models have been introduced

- data/DataSyncWorkflow
- data/UserSyncSource
- data/UserFieldMapping
- relation/User
- view/UserProvisioningStatus

The following models have been updated ([see updated schema](#))

- data/User

## RBAC and Configuration Changes

On upgrading to version 20.1.1, a migration will make updates to all of the following

- Data Syncs
- Menu Layouts
- Landing Pages
- Access Profiles
- Configuration Templates
- Field Display Policies

## Data Syncs

### **Updated**

Certain Data Sync instances are automatically updated to change the workflows being called:

- HcsLdapUserPurge--X
  - HcsPurgeLdapUserEvtPWF --> UserLdapSyncPurge
- HcsUserPhonePurgeDS-[host]--[customer-cluster]
  - HcsAddCucmUserDsPWF --> UserCucmSyncAdd
  - HcsUpdateCucmUserDsPWF --> UserCucmSyncUpdate
  - HcsDeleteCucmUserDsPWF --> UserCucmSyncRemove
- HcsPull-[host]--[customer-cluster]
  - HcsAddCucmUserDsPWF --> UserCucmSyncAdd
  - HcsUpdateCucmUserDsPWF --> UserCucmSyncUpdate
  - HcsDeleteCucmUserDsPWF --> UserCucmSyncRemove
- HcsPurgeDS-[host]--[customer-cluster]
  - HcsDeleteCucmUserDsPWF --> UserCucmSyncRemove
- HcsUserPurgeDS-[host]--[customer-cluster]
  - HcsAddCucmUserDsPWF --> UserCucmSyncAdd
  - HcsUpdateCucmUserDsPWF --> UserCucmSyncUpdate
  - HcsDeleteCucmUserDsPWF --> UserCucmSyncRemove

- HcsUserSyncDS-[host]--[customer-cluster]
  - HcsAddCucmUserDsPWF --> UserCucmSyncAdd
  - HcsUpdateCucmUserDsPWF --> UserCucmSyncUpdate
  - HcsDeleteCucmUserDsPWF --> UserCucmSyncRemove

## Menu Layouts

### Removed

- LDAP Management --> LDAP Authentication Users
- User Management --> Provisioning Status
- User Management --> Manage Users

Any menu items configured to reference the following models are automatically removed from the corresponding menu layout

- data/NormalizedUser
- data/HcsUserProvisioningStatusDAT
- data/LdapUser
- data/SsoUser
- data/UserAuthMethod
- data/HcsAdminUserDAT
- relation/HcsUserREL
- relation/HcsAdminUserREL

### Added

- User Management --> User Field Mapping
- User Management --> Advanced --> LDAP Users (person)
- User Management --> Advanced --> LDAP Users (InetOrgPerson)
- User Management --> Advanced --> CUC Users (User)
- User Management --> Advanced --> UCCX Users (Agent)
- User Management --> Advanced --> WEBEX Teams Users (User)

### Updated

- User Management --> Advanced --> LDAP Users (AD Only) to User Management --> Advanced --> LDAP Users (user)

- User Management --> Advanced --> CUCM Users to User Management --> Advanced --> CUCM Users (User)
- User Management --> Advanced --> Convert User Type: CUCM-LDAP to CUCM Local to User Management --> Advanced --> Convert to Local CUCM user

## Landing Pages

Any landing page links configured to reference the following models are automatically removed from the corresponding landing page

- data/NormalizedUser
- data/HcsUserProvisioningStatusDAT
- data/LdapUser
- data/SsoUser
- data/UserAuthMethod
- data/HcsAdminUserDAT
- relation/HcsUserREL
- relation/HcsAdminUserREL

## Access Profiles

Permissions for all of the following models are automatically removed from all access profiles

- data/NormalizedUser
- data/HcsUserProvisioningStatusDAT
- data/LdapUser
- data/SsoUser
- data/UserAuthMethod
- data/HcsAdminUserDAT
- relation/HcsUserREL
- relation/HcsAdminUserREL

## Configuration Templates

Configuration Templates for all the following models are automatically deleted

- data/NormalizedUser
- data/HcsUserProvisioningStatusDAT
- data/LdapUser
- data/SsoUser
- data/UserAuthMethod
- data/HcsAdminUserDAT
- relation/HcsUserREL
- relation/HcsAdminUserREL

## Field Display Policies

Field Display Policies for all the following models are automatically deleted

- data/NormalizedUser
- data/HcsUserProvisioningStatusDAT
- data/LdapUser
- data/SsoUser
- data/UserAuthMethod
- data/HcsAdminUserDAT
- relation/HcsUserREL
- relation/HcsAdminUserREL

Field Display Policies for the following models have been updated to account for the new schemas

- data/User
- relation/Subscriber

## Number Inventory

Number Inventory in 20.1.1 has been updated to

- Improve the tracking of numbers
- Introduce the ability to reserve numbers
- Consolidate interfaces for adding number ranges between Enterprise and Provider deployments

### Schema changes

#### Status

The schema of data/InternalNumberInventory has been updated to replace the boolean attributes “used” and “available” with a new string attribute, “status”, with the following valid values:

- Available
- Used
- Used-Utility
- Reserved
- Cooling

## Usage

The schema of data/InternalNumberInventory has been updated to introduce a new string attribute, "usage", indicating the type of device or utility which is consuming the INI instance (if any).

DN Use	Device	New Status	Usage	Vendor
<b>Not Used by anything</b>		Available	"blank"	
<b>Phone Line</b>	device/cucm/Phone (line instance)	Used	<b>Device</b> (Used to represent Phone, Device Profiles or Remote Destination Profile)	
<b>Device Profile Line</b>	device/cucm/DeviceProfile (line instance)	Used	<b>Device</b> (Used to represent Phone, Device Profiles or Remote Destination Profile)	

<b>RemoteDestination Profile Line</b>	device/cucm/RemoteDestinationProfile (line instance)	Used	<b>Device</b> (Used to represent Phone, Device Profiles or Remote Destination Profile)	
<b>Hunt Pilot</b>	device/cucm/HuntPilot	Used-Utility	<b>Hunt_Pilot</b>	
<b>Pickup Group Pilot</b>	device/cucm/CallPickupGroup	Used-Utility	<b>Pickup_Group_Pilot</b>	
<b>System Call Handler</b>	device/cuc/Callhandler (System only)	Used-Utility	<b>Call_Handler_Pilot</b>	
<b>VoiceMailPilot</b>	device/cucm/VoicemailPilot	Used-Utility	<b>Voicemail_Pilot</b>	
<b>Meet Me</b>	device/cucm/MeetMe	Used-Utility	<b>Meet_Me</b>	
<b>CTI Route Point</b>	device/cucm/CtiRoutePoint	Used-Utility	<b>CTI_RoutePoint</b>	
<b>Call Park</b>	device/cucm/CallPark	Used-Utility	<b>Call_Park</b>	
<b>Directed Call Park</b>	device/cucm/DirectedCallPark	Used-Utility	<b>Directed_Call_Park</b>	
<b>VOSS Phone</b>	data/GS_Shout_MultiVendorPhone_DAT	Used-Utility	<b>VOSS_Phone</b>	<b>VOS S</b>

## Release Date

The schema of data/InternalNumberInventory has been updated to replace the string attribute “cooling\_end\_date” with a new date string attribute, “release\_date”, indicating the date when a number will be released if either cooling or reserved.

## Vendor

The schema of `data/InternalNumberInventory` has been updated to introduce a new string attribute, “`vendor`”, indicating the vendor of the device using the number e.g. Cisco, Microsoft etc.

## Model Changes

- `data/InternalNumberInventory` will remain but any Menus and Access Profiles referring to the data model directly will be updated to use the new relation:  
**relation/NumberInventoryREL**
- The view for adding Internal Numbers in Provider deployments:  
**view/HcsDNMgmtVIEW**  
has been replaced with a new view which now supports Add, Update and Delete:  
**view/NumberInventoryRangeMgmtVIEW**
- The view for managing internal Numbers in Enterprise deployments:  
**view/UcsMaintainMultiInternalNumberInventoryVIEW**  
has been replaced with the same new view:  
**view/NumberInventoryRangeMgmtVIEW**
- The view used for auditing number inventory:  
**view/HcsDNIventoryMgmtView**  
has been replaced with a new view:  
**view/NumberInventoryAudit**

## Migration

On upgrade the `data/InternalNumberInventory` instances will be migrated as follows:

Existing Values	New Friendly Value	New Data (actual) Value
-----------------	--------------------	-------------------------

Used = True, Available = True	Used	used
Used = True, Available = False	Used-Utility	used_util
Used = False, Available = True	Available	available
Used = False, Available = False and Cooling Date not Empty	Cooling	cooling
Used = False, Available = False and Cooling Date is Empty	Reserved	reserved

## **Adaptations**

If you are making use of any adaptations, please contact your VOSS account manager for updated versions that are compatible with these changes.

## Appendix A - data/User Schema

```
{  
    "meta": {  
        "hierarchy": "sys",  
        "model_type": "data/DataModel",  
        "tags": [  
            "user",  
            "useroverhaul"  
        ],  
        "version_tag": "7.0.0"  
    },  
    "data": {  
        "Meta": {  
            "attr_props": [  
                {  
                    "description": "The username corresponding to the the Username in  
Cisco Unified Communications Manager and Cisco Unity Connection server.",  
                    "name": "username",  
                    "required": true,  
                    "title": "User Name",  
                    "type": "string"  
                },  
                {  
                    "description": "The email address corresponding to the the  
Username in Cisco Unified Communications Manager and Cisco Unity Connection server.",  
                    "name": "email",  
                    "required": false,  
                    "title": "Email Address",  
                    "type": "string"  
                },  
                {  
                    "description": "The first name corresponding to the user first  
name in Cisco Unified Communications Manager and Cisco Unity Connection server.",  
                    "name": "first_name",  
                    "title": "First Name",  
                    "type": "string"  
                },  
                {  
                    "description": "The last name corresponding to user last name in  
Cisco Unified Communications Manager and Cisco Unity Connection server.",  
                    "name": "last_name",  
                    "title": "Last Name",  
                    "type": "string"  
                }  
            ]  
        }  
    }  
}
```

```

},
{
    "description": "The password corresponding to the user password in
Cisco Unified Communications Manager. The password is hidden.",
    "is_password": true,
    "name": "password",
    "pattern": ".{8,}",
    "title": "Password",
    "type": "string"
},
{
    "description": "The role to which the user belongs. See: Role.",
    "format": "uri",
    "name": "role",
    "required": true,
    "target": "data/Role",
    "target_attr": "name",
    "title": "Role",
    "type": "string"
},
{
    "default": "en-us",
    "description": "The preferred language for this user.",
    "format": "uri",
    "name": "language",
    "required": false,
    "target": "data/Language",
    "target_attr": "lcid",
    "title": "Language",
    "type": "string"
},
{
    "default": false,
    "description": "Indicate if the user's language is set by language
default in the hierarchy.",
    "name": "set_language",
    "required": false,
    "title": "Set by Default Language",
    "type": "boolean"
},
{
    "attr_props": [
        {
            "description": "Indicates if the user must be forced to
change their password the next time that login.",
            "name": "change_password_on_login",
            "required": false,
            "title": "Change Password on Next Login",
        }
    ]
}

```

```

        "type": "boolean"
    },
{
    "description": "Indicates if the account has been locked
to prevent the user from logging in.",
    "name": "locked",
    "required": false,
    "title": "Locked",
    "type": "boolean"
},
{
    "description": "Indicates if the account has been disabled
to prevent the user from logging in until an administrator enables the account
again.",
    "name": "disabled",
    "required": false,
    "title": "Disabled",
    "type": "boolean"
},
{
    "description": "A description of why the account is
disabled.",
    "name": "reason_for_disabled",
    "required": false,
    "title": "Reason for Disabled",
    "type": "string"
},
{
    "description": "Specifies the policy with the rules used
to govern this user's credentials.",
    "format": "uri",
    "name": "credential_policy",
    "required": false,
    "target": "data/CredentialPolicy",
    "target_attr": "name",
    "title": "Credential Policy",
    "type": "string"
},
{
    "description": "The time when the user account was locked
as result of the number of failed login attempts exceeding the permitted thresholds.",
    "format": "date-time",
    "name": "failed_login_lock_date",
    "required": false,
    "title": "Time Locked Due to Failed Login Attempts",
    "type": "string"
},
{

```

```

    "description": "The time when the password was last
changed.",
    "format": "date-time",
    "name": "password_last_change_time",
    "readonly": true,
    "required": false,
    "title": "Time of Last Password Change",
    "type": "string"
},
{
    "description": "The time when the password was last
changed by the user.",
    "format": "date-time",
    "name": "password_last_change_time_by_user",
    "readonly": true,
    "required": false,
    "title": "Time of Last Password Change By User",
    "type": "string"
},
{
    "description": "The time the user last logged in
successfully.",
    "format": "date-time",
    "name": "last_login_time",
    "readonly": true,
    "required": false,
    "title": "Time of Last Successful Login",
    "type": "string"
},
{
    "default": "0",
    "description": "The total number of failed login attempts
since last successful login.",
    "name": "num_of_failed_login_attempts",
    "required": false,
    "title": "Number of Failed Login Attempts Since Last
Successful Login",
    "type": "integer"
},
{
    "items": {
        "attr_props": [
            {
                "displayable": true,
                "maxLength": 128,
                "name": "question",
                "required": true,
                "title": "Question",
                "type": "string"
            }
        ]
    }
}

```

```

        "type": "string"
    },
    {
        "maxLength": 128,
        "name": "answer",
        "required": true,
        "title": "Answer",
        "type": "string"
    }
],
"type": "object"
},
"name": "security_questions",
"title": "Security Questions",
"type": "array"
},
{
"description": "List of passwords that have been used by
user.",
"items": [
    "attr_props": [
        {
            "description": "Used password",
            "name": "password",
            "title": "Password",
            "type": "string"
        },
        {
            "description": "Time when password was
created.",
            "name": "time_created",
            "title": "Time Created",
            "type": "string"
        }
    ],
    "type": "object"
},
{
"name": "used_passwords",
"title": "Used Passwords",
"type": "array"
}
],
"description": "Additional account information for the given
user.",
"name": "account_information",
"required": false,
"title": "Account Information",
"type": "object"

```

```

},
{
    "displayable": false,
    "format": "uri",
    "is_password": false,
    "maxLength": 1024,
    "name": "entitlement_profile",
    "readonly": false,
    "required": false,
    "target": "data/HcsEntitlementProfileDAT",
    "title": "Entitlement Profile",
    "type": "string"
},
{
    "description": "Sync source of the user. Identifies where the user was synced from. This value will determine the master of the data. The data in the User model will be derived from the fields of the master application (E.G. CUCM, CUC, MS-LDAP).",
    "format": "uri",
    "name": "sync_source",
    "target": "data/UserSyncSource",
    "target_attr": "name",
    "default": "LOCAL",
    "title": "Sync Source",
    "type": "string"
},
{
    "description": "Building name or number.",
    "name": "building_name",
    "title": "Building Name",
    "type": "string"
},
{
    "description": "Country name.",
    "name": "country",
    "title": "Country",
    "type": "string"
},
{
    "description": "Department names and numbers.",
    "name": "department",
    "title": "Department",
    "type": "string"
},
{
    "description": "Alphanumeric Directory URI (e.g. SIP URI)",
    "name": "directory_uri",
    "title": "Directory URI",
}

```

```

        "type": "string"
    },
{
    "description": "Display name of the user",
    "name": "display_name",
    "title": "Display Name",
    "type": "string"
},
{
    "description": "Employee number of the user",
    "name": "employee_number",
    "title": "Employee Number",
    "type": "string"
},
{
    "description": "Employee type",
    "name": "employee_type",
    "title": "Employee Type",
    "type": "string"
},
{
    "description": "Facsimile Telephone Number",
    "items": {
        "type": "string"
    },
    "name": "facsimile_telephone_number",
    "title": "Facsimile Telephone Number",
    "type": "array"
},
{
    "description": "Contains strings that represent the user's home
phone number(s).",
    "items": {
        "type": "string"
    },
    "name": "home_phone",
    "title": "Home Phone",
    "type": "array"
},
{
    "description": "Contains strings that represent the user's IP
phone number(s).",
    "items": {
        "type": "string"
    },
    "name": "ip_phone",
    "title": "IP Phone",
    "type": "array"
}

```

```

},
{
  "description": "Jabber ID",
  "name": "jabber_id",
  "title": "Jabber ID",
  "type": "string"
},
{
  "description": "Contains the name of a person's locality.",
  "name": "city",
  "title": "City",
  "type": "string"
},
{
  "description": "Manager.",
  "name": "manager",
  "title": "Manager",
  "type": "string"
},
{
  "description": "The user can be a member of a variety of groups.",
  "items": {
    "type": "string"
  },
  "name": "member_of",
  "title": "Member Of",
  "type": "array"
},
{
  "description": "Contains strings that represent the user's IP
mobile number(s).",
  "items": {
    "type": "string"
  },
  "name": "mobile",
  "title": "Mobile",
  "type": "array"
},
{
  "description": "The name of the person's organization.",
  "name": "organization",
  "title": "Organization",
  "type": "string"
},
{
  "items": {
    "is_password": false,
    "type": "string"
  }
}

```

```

        },
        "minItems": 0,
        "name": "object_class",
        "title": "Object Class",
        "type": "array"
    },
    {
        "items": {
            "is_password": false,
            "type": "string"
        },
        "minItems": 0,
        "name": "other_mailbox",
        "title": "Other Mailbox",
        "type": "array"
    },
    {
        "description": "The name of the person's organization unit.",
        "items": {
            "is_password": false,
            "type": "string"
        },
        "minItems": 0,
        "name": "ou",
        "title": "Organizational Unit",
        "type": "array"
    },
    {
        "description": "Photo URL.",
        "name": "photo_url",
        "title": "Photo URL",
        "type": "string"
    },
    {
        "description": "Physical Delivery Office Name.",
        "name": "physical_delivery_office_name",
        "title": "Physical Delivery Office Name",
        "type": "string"
    },
    {
        "description": "Contains code used by a Postal Service to identify postal service zones.",
        "name": "postal_code",
        "title": "Postal Code",
        "type": "string"
    },
    {
        "description": "Preferred Language."
    }

```

```

        "name": "preferred_language",
        "title": "Preferred Language",
        "type": "string"
    },
    {
        "description": "Contains full names of state or province.",
        "name": "state",
        "title": "State",
        "type": "string"
    },
    {
        "description": "Contains site information from a postal address.",
        "name": "street",
        "title": "Street",
        "type": "string"
    },
    {
        "description": "Telephone Number.",
        "items": [
            {
                "type": "string"
            },
            {
                "name": "telephone_number",
                "title": "Telephone Number",
                "type": "array"
            }
        ],
        {
            "description": "Timezone.",
            "name": "timezone",
            "title": "Timezone",
            "type": "string"
        },
        {
            "description": "Title.",
            "name": "title",
            "title": "Title",
            "type": "string"
        },
        {
            "description": "Unverified Mail Box.",
            "name": "unverified_mailbox",
            "title": "Unverified Mail Box",
            "type": "string"
        },
        {
            "description": "Custom String",
            "name": "customString1",
            "title": "Custom String 1",
            "type": "string"
        }
    }
]
```

```
},
{
    "description": "Custom String",
    "name": "customString2",
    "title": "Custom String 2",
    "type": "string"
},
{
    "description": "Custom String",
    "name": "customString3",
    "title": "Custom String 3",
    "type": "string"
},
{
    "description": "Custom String",
    "name": "customString4",
    "title": "Custom String 4",
    "type": "string"
},
{
    "description": "Custom String",
    "name": "customString5",
    "title": "Custom String 5",
    "type": "string"
},
{
    "description": "Custom String",
    "name": "customString6",
    "title": "Custom String 6",
    "type": "string"
},
{
    "description": "Custom String",
    "name": "customString7",
    "title": "Custom String 7",
    "type": "string"
},
{
    "description": "Custom String",
    "name": "customString8",
    "title": "Custom String 8",
    "type": "string"
},
{
    "description": "Custom String",
    "name": "customString9",
    "title": "Custom String 9",
    "type": "string"
}
```

```

},
{
    "description": "Custom String",
    "name": "customString10",
    "title": "Custom String 10",
    "type": "string"
},
{
    "description": "Custom List of Strings",
    "items": {
        "type": "string"
    },
    "name": "customListOfStrings1",
    "title": "Custom List of Strings 1",
    "type": "array"
},
{
    "description": "Custom List of Strings",
    "items": {
        "type": "string"
    },
    "name": "customListOfStrings2",
    "title": "Custom List of Strings 2",
    "type": "array"
},
{
    "description": "Custom List of Strings",
    "items": {
        "type": "string"
    },
    "name": "customListOfStrings3",
    "title": "Custom List of Strings 3",
    "type": "array"
},
{
    "description": "Custom List of Strings",
    "items": {
        "type": "string"
    },
    "name": "customListOfStrings4",
    "title": "Custom List of Strings 4",
    "type": "array"
},
{
    "description": "Custom List of Strings",
    "items": {
        "type": "string"
    },

```

```

        "name": "customListOfStrings5",
        "title": "Custom List of Strings 5",
        "type": "array"
    },
    {
        "description": "Custom List of Strings",
        "items": {
            "type": "string"
        },
        "name": "customListOfStrings6",
        "title": "Custom List of Strings 6",
        "type": "array"
    },
    {
        "description": "Custom List of Strings",
        "items": {
            "type": "string"
        },
        "name": "customListOfStrings7",
        "title": "Custom List of Strings 7",
        "type": "array"
    },
    {
        "description": "Custom List of Strings",
        "items": {
            "type": "string"
        },
        "name": "customListOfStrings8",
        "title": "Custom List of Strings 8",
        "type": "array"
    },
    {
        "description": "Custom List of Strings",
        "items": {
            "type": "string"
        },
        "name": "customListOfStrings9",
        "title": "Custom List of Strings 9",
        "type": "array"
    },
    {
        "description": "Custom List of Strings",
        "items": {
            "type": "string"
        },
        "name": "customListOfStrings10",
        "title": "Custom List of Strings 10",
        "type": "array"
    }
}

```

```
},
{
    "description": "Custom Boolean",
    "name": "customBoolean1",
    "title": "Custom Boolean 1",
    "type": "boolean"
},
{
    "description": "Custom Boolean",
    "name": "customBoolean2",
    "title": "Custom Boolean 2",
    "type": "boolean"
},
{
    "description": "Custom Boolean",
    "name": "customBoolean3",
    "title": "Custom Boolean 3",
    "type": "boolean"
},
{
    "description": "Custom Boolean",
    "name": "customBoolean4",
    "title": "Custom Boolean 4",
    "type": "boolean"
},
{
    "description": "Custom Boolean",
    "name": "customBoolean5",
    "title": "Custom Boolean 5",
    "type": "boolean"
},
{
    "description": "Custom Boolean",
    "name": "customBoolean6",
    "title": "Custom Boolean 6",
    "type": "boolean"
},
{
    "description": "Custom Boolean",
    "name": "customBoolean7",
    "title": "Custom Boolean 7",
    "type": "boolean"
},
{
    "description": "Custom Boolean",
    "name": "customBoolean8",
    "title": "Custom Boolean 8",
    "type": "boolean"
}
```

```

},
{
    "description": "Custom Boolean",
    "name": "customBoolean9",
    "title": "Custom Boolean 9",
    "type": "boolean"
},
{
    "description": "Custom Boolean",
    "name": "customBoolean10",
    "title": "Custom Boolean 10",
    "type": "boolean"
},
{
    "choices": [
        {
            "title": "Local",
            "value": "Local"
        },
        {
            "title": "Automatic",
            "value": "Automatic"
        },
        {
            "title": "LDAP",
            "value": "LDAP"
        },
        {
            "title": "SSO",
            "value": "SSO"
        }
    ],
    "default": "Local",
    "description": "The type of authentication that our user would be using. Typically this would be choices between a Standard VOSS 4 UC user, an LDAP user or an SSO user.",
    "name": "auth_method",
    "title": "Auth Method",
    "type": "string"
},
{
    "description": "A reference to the LDAP server which this user must authenticate against.",
    "format": "uri",
    "name": "ldap_server",
    "required": false,
    "target": "data/Ldap",
    "title": "LDAP Server",
}

```

```

        "type": "string"
    },
{
    "description": "The login attribute of the associated LDAP device
model instance",
    "name": "ldap_username",
    "title": "LDAP Username",
    "type": "string"
},
{
    "description": "The entity id of the SSO Identity Provider.",
    "format": "uri",
    "name": "sso_idp",
    "required": false,
    "target": "data/SsoIdentityProvider",
    "target_attr": "entity_id",
    "title": "SSO Identity Provider",
    "type": "string"
},
{
    "description": "The name identifier that is used for an SSO
authenticated user.",
    "name": "sso_username",
    "required": false,
    "title": "SSO Username",
    "type": "string"
},
{
    "choices": [
        {
            "title": "Admin",
            "value": "Admin"
        },
        {
            "title": "End User",
            "value": "End User"
        }
    ],
    "default": "Admin",
    "description": "Indicate the user's login type.",
    "name": "user_type",
    "required": false,
    "title": "User Type",
    "type": "string"
},
{

```

```

    "description": "Exclude from Directory flag to control the Phone
Services directory lookup. If set to true the User's phone number will not appear in
the directory lookup.",
        "name": "exclude_from_directory",
        "title": "Exclude from Directory",
        "type": "boolean"
    }
],
"constraints": [
{
    "business_key": true,
    "hierarchy": true,
    "unique": [
        "username"
    ]
},
{
    "business_key": true,
    "hierarchy": false,
    "unique": [
        "email"
    ]
}
],
"operations": [
    "get",
    "list",
    "add",
    "clone",
    "update",
    "remove",
    "export_bulkload_template",
    "bulk_update_form",
    "configuration_template",
    "field_display_policy",
    "export",
    "migration",
    "help",
    "tag",
    "tag_version"
],
"summaryAttrs": [
    "username",
    "last_name",
    "first_name",
    "email",
    "role",
    "entitlement_profile",

```

```

        "sync_source",
        "user_type",
        "auth_method",
        "department"
    ],
},
"doc": "The User model for user details that correspond with Cisco Unified Communications Manager and Cisco Unity Connection server.",
"name": "User"
}
}

```

## Appendix B - data/InternalNumberInventory Schema

```
{
"meta": {
    "model_type": "data/DataModel",
    "version_tag": "1.8",
    "tags": [
        "ini",
        "inicooling"
    ]
},
"data": {
    "name": "InternalNumberInventory",
    "doc": "The DataModel that V4UC uses to manageINI items.",
    "Meta": {
        "operations": [
            "add",
            "bulk_update_form",
            "configuration_template",
            "export",
            "export_bulkload_template",
            "field_display_policy",
            "get",
            "help",
            "list",
            "migration",
            "remove",
            "tag",
            "tag_version",
            "update",
            "validate"
        ]
    }
}
}
```

```

        "move"
],
"list_operations": [
    "ReserveNumber"
],
"summaryAttrs": [
    "internal_number",
    "status",
    "usage",
    "e164number",
    "release_date",
    "tag",
    "description",
    "reservation_notes",
    "vendor",
    "extra1",
    "extra2",
    "extra3",
    "extra4",
    "extra5",
    "extra6"
],
"attrProps": [
    {
        "required": true,
        "type": "string",
        "name": "internal_number",
        "title": "Internal Number"
    },
    {
        "name": "status",
        "title": "Status",
        "required": true,
        "type": "string",
        "choices": [
            {
                "title": "Available",
                "value": "Available"
            },
            {
                "title": "Used",
                "value": "Used"
            },
            {
                "title": "Used-Utility",
                "value": "Used-Utility"
            }
        ]
    }
]

```

```

        "title": "Reserved",
        "value": "Reserved"
    },
    {
        "title": "Cooling",
        "value": "Cooling"
    }
]
},
{
    "name": "usage",
    "title": "Usage",
    "type": "string"
},
{
    "name": "reservation_notes",
    "title": "Reservation notes",
    "type": "string"
},
{
    "name": "release_date",
    "title": "Release Date",
    "description": "A value indicates that the number is in temporary 'cooldown' isolation (and therefore also temporarily unavailable until the cooling duration expires, refer to global settings).",
    "help_text": "A value here indicates that the number is in temporary 'cooldown' isolation and therefore also temporarily unavailable until the cooling duration expires (refer to global settings).",
    "type": "string"
},
{
    "type": "string",
    "name": "tag",
    "title": "Tag"
},
{
    "type": "string",
    "name": "description",
    "title": "Description"
},
{
    "type": "string",
    "name": "e164number",
    "title": "E164Number"
},
{
    "type": "string",
    "name": "vendor",

```

```
        "title": "Vendor"
    },
{
    "type": "string",
    "name": "extra1",
    "title": "Extra1"
},
{
    "type": "string",
    "name": "extra2",
    "title": "Extra2"
},
{
    "type": "string",
    "name": "extra3",
    "title": "Extra3"
},
{
    "type": "string",
    "name": "extra4",
    "title": "Extra4"
},
{
    "type": "string",
    "name": "extra5",
    "title": "Extra5"
},
{
    "type": "string",
    "name": "extra6",
    "title": "Extra6"
},
{
    "type": "string",
    "name": "extra7",
    "title": "Extra7"
},
{
    "type": "string",
    "name": "extra8",
    "title": "Extra8"
},
{
    "type": "string",
    "name": "extra9",
    "title": "Extra9"
}
],

```

```
        "constraints": [
            {
                "hierarchy": true,
                "unique": [
                    "internal_number"
                ],
                "business_key": true
            }
        ]
    }
}
```